





Rails

		•	4.5
(= ANARA	In	OKM	ation:
General			alion.

Company name			
Person to contact			
Position			
E-mail address			
Phone no.		Fax no.	
Address			
Your SGM Contact	Name:	Email	
	Phone no.	Fax no.	

Rail Layer Specifications:

Please detail rail profile specification	(s) as per your denomination	standards:
Length(s) meters/feet		
Weight(s) kg/lbs.		
Rail layer composition	Qty.	per profile mm/inches
	Qty.	per profile mm/inches
	Qty.	per profile mm/inches
	Qty.	per profile mm/inches
Temperature	☐ Ambient	☐ Hot (>150°C/300°F)
For hot rails only		
Standard surface temperature	°C/°F	
Maximum surface temperature	°C/°F	_



SGM MAGNETICS Enquiry form



Crane model						
☐ Bridge crane		ouble	leg crane			
☐ Else, please	specify:					
Crane rated vol						
Crane working	environment	□ Inc	loor Outdoor			
Crane type and	d capacity					
☐ Single hoist ☐Two		hoists		ndent hoists		
6			HOOK 1	100K2	HOOK 1	
Capacity	Metric tor	าร	Capacity 1	Metric tons	Capacity 1	Metric tons
			Capacity 2	Metric tons	Capacity 2	Metric tons
			Set distance mm/inches			
emarks:						
Preferred solut				T		
☐ Electro-magr				☐ Battery back-	-up requested	
☐ Electro-perm		et <u> </u>				
☐ No preference	е					
Cable reel:			1			
☐ Not requeste	ed .		☐ Requeste	d, stroke	meters/feet	
otes:						