

SGM MAGNETICS Enquiry form



Wire rolls

			****		3		
Seneral Information:							
Company name							
Person to contact							
Position							
E-mail address							
Phone no.					Fax no		
Address							
Your SGM Contact	Name:			Email			
	Phone no).			Fax no.		
pplication:							
☐ Production ☐ Stockis		st		☐ Other, please spe		specify:	
pecifications:							
~ ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~							
/ /////////////////////////////////////							
	\\\\ \\\\					 -	~_
/ <i>////</i>							
\	<i>}}}}}</i>						
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\							
□ Horizon	otal ava					rtical ava	
☐ Horizon	ılai eye				⊔ ve	rtical eye	
Length		Min.	mm/in	iches		Max.	mm/inches
Inner diameter		Min.	mm/in	ches		Max.	mm/inches
Outer diameter		Min.	mm/in	ches		Max.	mm/inches
Wire section		Min.	mm/in	ches		Max.	mm/inches
Weight		Min.	kg/lbs			Max.	kg/lbs.
			I Ambient			☐ Hot (>150 °C / 300 °F)
For hot coils only							· · · · · · · · · · · · · · · · · · ·
Standard surface temperatu	ıre °C/	°F					
Maximum surface temperat	ure °C/	°F					
Banding							
Туре				☐ Stra	aps 🗆	l Wires	
Tightness				-	•	ose and adju	stable
			☐ Loose and non-adjustable				



SGM MAGNETICS Enquiry form



	Maximum quantity of rolls to be lifted at a time:								
	For multiple roll-lift only								
	Maximum quantity of rolls per length		Qty. x length						
	Rolls to be lifted are positioned		☐ in a row ☐ side by side						
C	rane specifications:								
	Crane capacity Metric tons/US tons								
	Crane rated voltage		□ Vac □ Vdc						
	Crane working environment		☐ Indoor ☐ Outdoor						
R	emarks:								
	☐ Battery back-up requested								
	Cable reel:								
	☐ Not requested	☐ Requested,	, stroke meters/feet						
N	otes:								